

**IEC Mineral Insulated Thermocouple with Plain
Pot Seal, 1m of PFA Insulated IEC Lead and Mini
Plug Termination - Type T - 3.0mm x 150mm**

Image
Coming
Soon

Need Your Temperature Sensor calibrated?

Traceable to ISO17025 (UKAS) calibration standards, Labfacility offer a choice of a 3 or 5 point traceable calibration using our in-house calibration facility.

Please be aware that if you add a calibration option to your order you will be contacted regarding delivery information.

Specifications**Specifications**

Product Code	XE-0350-001
General Description	Plain pot seal (200°C) with 1 Metre of PFA insulated lead, 7/0.2mm flat pair with tails.
Sensor Type	Mineral Insulated
Thermocouple Type	T
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	3.0mm
Probe Length	150mm
Sheath Material	Stainless steel 316
Pot Type	Plain (+200°C)
Cable Length	1m
Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to IEC 584)
Core / Strands	7/0.2mm
Termination Type	Fitted mini plug



Max. Temperature	+400°C
Min. Temperature	-100°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584
Connector Type	Plug
Connector Size	Miniature
Colour	Brown